



American Society of Naval Engineers (ASNE) Combat Systems Symposium 2012 Arlington, VA

Balancing Capacity vs. Capability

Laser Weapons for Naval Applications

Dr. Phillip Sprangle

Naval Research Laboratory

March 27, 2012

| maintaining the data needed, and c including suggestions for reducing | lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number. | ion of information. Send comments arters Services, Directorate for Information | regarding this burden estimate rmation Operations and Reports | or any other aspect of the property of the pro | his collection of information, Highway, Suite 1204, Arlington | |
|--|--|--|--|--|--|--|
| 1. REPORT DATE 26 MAR 2012 | 2 DEPORT TYPE | | | 3. DATES COVERED 00-00-2012 to 00-00-2012 | | |
| 4. TITLE AND SUBTITLE | | | | 5a. CONTRACT NUMBER | | |
| Laser Weapons for Naval Applications | | | | 5b. GRANT NUMBER | | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | | |
| 6. AUTHOR(S) | | | | 5d. PROJECT NUMBER | | |
| | | | | 5e. TASK NUMBER | | |
| | | | | 5f. WORK UNIT NUMBER | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory, Washington, DC, 20375 | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER | | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | | |
| | | | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | |
| 12. DISTRIBUTION/AVAIL Approved for publ | LABILITY STATEMENT ic release; distributi | on unlimited | | | | |
| 13. SUPPLEMENTARY NO Presented at : Com VA | otes abat Systems Sympo | sium 2012: March 2 | 26-27, 2012, Shera | aton Nationa | l Hotel, Arlington, | |
| 14. ABSTRACT | | | | | | |
| 15. SUBJECT TERMS | | | | | | |
| 16. SECURITY CLASSIFIC | | 17. LIMITATION OF | 18. NUMBER | 19a. NAME OF | | |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | Same as Report (SAR) | OF PAGES 21 | RESPONSIBLE PERSON | |

Report Documentation Page

Form Approved OMB No. 0704-0188



Outline



- Background
- Laser candidates
 - Free electron lasers
 - Solid state lasers
- Additional capabilities
 - Power beaming





Laser Lethality

- Thermally ablating 1/4 pound of target material requires ~ 1.3 MJ of laser energy
- 1 MJ is equivalent to $\sim 1/2$ pound of explosive
- 100 kW of <u>absorbed</u> laser power for 2 sec ablates ~ 20 grams (~ 8 pennies)
- For an engagement time of 5 sec the required laser power is > 250kW






Capabilities of Laser Weapons

- Agile speed of light delivery (instantaneous)
- All electric energy source (deep magazines)
- Long range targeting
- Multi-targeting
- Compatible with all electric ships





Extinction Coefficient vs Wavelength Maritime Atmosphere



Maritime Windows

 $\sim 1 \mu m$ $\sim 1.25 \ \mu m$ $\sim 1.6 \ \mu m$ $\sim 2.1 \text{--} 2.3 \ \mu m$





Laser Systems for Naval Applications

- Free Electron Lasers
 - Jefferson Lab. $P > 14 \text{ kW}, \ \lambda \sim 1.6 \ \mu\text{m}$

- Solid State Lasers
 - IPG fiber lasers, 10 kW/fiber
 - Northrop Grumman JHPSSL

100 kW (2011), 7 tiles
$$\lambda = 1.06 \mu m \text{ (N}_d:YAG)$$



Free Electron Lasers




- High average power capability
- Output wavelength is tunable (can operate in atmospheric window)
- Wall-plug efficiency ~ 10% (potentially)
- Dimension ~ 4 m x 4m x 30m, for 100kW to ~ 1 MW
- Ship power requirements > 10 MW (engagement time ~ 10s of minutes)









- Electrons undulate in wiggler field and bunch at optical wavelength
- Optical radiation is amplified

Example:
$$\lambda_w = 3 \,\text{cm}$$
, $E_b = 80 \,\text{MeV}$ $\lambda \approx 1 \,\mu m$

Goal:
$$\langle P \rangle \sim 1 \text{MW}$$
 $\lambda = 1 \mu m$, $1.6 \mu m$, $2.3 \mu m$





Fiber Lasers

Compact

• High-Power
$$P_{\text{fiber}} = \begin{cases} 8 \, \text{kW, commercial ly available} \\ 10 \, \text{kW, state-of-the-art} \end{cases}$$

- Robust
- High Wall Plug Efficiency (> 30 %)
- High Optical Quality



Fiber Laser




(1 kW, 1.6 kW, 1.6 kW and 2 kW)





Incoherent Combining of Fiber Lasers






- NRL Memorandum Report -6790-06-8963; also JDE 2, 273 (2007)
- U.S. Patent # 7,970,040 B1 (June, 2011)
- IEEE Journal of Quantum Electronics, 45, No. 2 (2009)





Four Incoherently Combined Fiber Lasers (NRL), 1.2 km Range

3 kW transmitted, 2.8 kW on target, 11/02/07








Starfire Optical Range (NRL) Propagation Range 3.2 km

Incoherently combined fiber lasers, ~ 5 kW, cw, $M^2 \sim 1$






Navy Laser Weapon System (LaWS)



• Based on the successful results of the NRL fiber laser program, the Laser Weapon System (LaWS) program (classified) was started in 2008 by NAVSEA, PMS 405

Power per fiber $\sim 5 \text{ kW}$





• Successfully tracked, engaged, and destroyed a UAV while in flight (May 24, 2010)



500 kW Fiber Laser Weapon System



• Laser power, CW:

$$P = 500 \,\mathrm{kW}$$

- # of Fiber lasers : N = 63 ($P_{\text{fiber}} = 8 \text{ kW}$, incoherently combined)
- Wall plug efficiency ~ 30 %
- Beam director: $R_{BD} = \sqrt{N} R_o \approx 50 \,\mathrm{cm}$
- Volume of optics $\approx 8 \,\mathrm{m}^3$
- Weight of optics $\approx 10,000 \, \text{lbs}$.

excluding power supply and cooling

• Water cooling ~ 1,000 gallons/min.







- Joint High Power Solid State Lasers (JHPSSL)
- Wavelength, 1.06 μm
- Power achieved 105 kW (2009) Northrop Grumman
- Wall-plug efficiency, 20%
- Modular design
- Compact



Laser Power Beaming New Operational Capabilities for the Navy/DoD



- Multiple kilowatts over multiple kilometers
- Laser power converters can be highly efficient, > 60 %

• Fiber lasers are highly compact and efficient making them ideal for this application

High-Power

CW Fiber Laser

Power converter 0.5 - 2 kW required Laser Beam Atmospheric Director Turbulence


Power beaming range $\sim 4 - 5 \text{ km}$




Laboratory Demonstration of Laser Power Beaming using Fiber Lasers



Semiconducting Convertor: InGaAs Spectrolab





- Efficiency ~ 42%
- 9 chips in series yields \sim 6 V, 8 A
- Total power \sim 12 x 48 W = 576 W







- Laser propagation in a maritime environment
 - turbulence
 - aerosols
 - thermal blooming
- Adaptive optics in deep turbulence
- Scalability to MW power levels
- Thermal management





Back Up Slides